

## SM-LED19A-2K 19" Professional LCD Monitor



### Key Features:

1. HD: 1920\*1080 with higher definition than the normal monitor.
2. Turn on the screen to automatically detect the resolution of the input signal in the lower left corner of screen.
3. Clear: delicate and realistic, conveying true colors, showing the true colors.
4. Bright: The quality is improved, only for better presentation.
5. Adopt industrial screen, high brightness, high contrast.
6. High-precision standard regulated power supply, specially designed for industrial equipment, supporting 24 hours × 365 days of uninterrupted work.
7. Adopt 10bit image chip processing technology, high pixel progressive scan, fine texture.
8. Support intelligent 3D noise reduction, eliminate afterimage function, dynamic brightness, contrast color optimization technology.
9. Apply the world's leading LED driver solution to accurately restore the front-end signal, with a strong sense of reality.
10. LED has small volume, low energy consumption, zero radiation, stable image, no impact on the eyes, natural health.
11. 5 ms extremely fast response, avoiding the tailing phenomenon of images in high speed operation.
12. Using nanotechnology, the picture is more three-dimensional, transparent.

### Specification

Product type	Professional Monitor
Product model	SM-LED19A-2K
Screen size	19"
Screen type	LCD
Screen ratio	16:10
Brightness	300 nit
Contrast ratio	3000:1
Response time	5 ms
Viewing area	408.24×255.15 mm
Viewing angle	wide
Display color	16.7M

Clearness	1920*1080
Control method	panel
Input port	HDMI, VGA, RCA, audio output
Audio output	with stereo speaker
Head set hole	audio input
Power supply	12V/2A
Total power	20W
Casing	fireproof plastic
Dimensions	436*290 not including the foot height (foot height: 82mm)
Installation method	base, wall mount
Product weight	2.5kg
Packing size	510mm*95mm*393mm
Gross weight	3.4kg
Packing size	5pcs in 1 case 555*500*435mm
Gross weight	18kg
Working environment temperature	20^C is the most suitable
Working environment humidity	10%-90%RH
Storage temperature	-20^C- 60^C

