Smart Outdoor PTZ IP Audio Camera

SM-PR5240-PT

Product Features

- H.265X 4MP mega pixels pan/tilt Wi-Fi IP camera
- HD 3.6mm LED distance 10-20m
- Support two-way audio intercom
- Support computer client remote / local viewing
- Auto motion track could pan 355 degree , tilt 90 degree
- 1 PCS power interface and reset button
- Support dual-stream, support 2.4GHz Wi-Fi distance 100 meters
- Support SD Card (Max 128GB)
- Support multiple mobile monitoring (iOS, Android) mobile APP: ”PROVIEW CCTV”
- Support three night vision modes : Infrared / Color / Smart Night Vision
- Plug and play, multiple network cloud services open security cloud monitoring
- Support automatic electric shutter function, adapt to different monitor environments
- Support alarm action (snapshot, take a video, device beep)
- Support motion alarm (humanoid detection switch, show traces, perimeter alert, cordon, alert area)
- Support ONVIF

Model		SM-PR5240-PT
Camera Features	Image Sensor	4MP 1/2.8" Low illumination CMOS Sensor
	Video Compression	H.265X coding,support dual stream,AVI;0.1M~8Mpbs variable
	Resolution	2560x1440
	Image Output	Main stream: 2560*1440@12fps, sub-stream: 640*360@25fps
	Min. Illumination	Color: 1.5 Lux; W/B: 0 Lux with IR LED ON
	Shutter	1/50(1/60) seconds to 1/100,000 seconds
	Focus Length	HD 3.6mm @F1.8
	Lens Mode	Fixed Lens
	Infrared LED	4 PCS IR + 4 PCS Warm LED
	Infrared Distance	10-20m
	Day/Night	Infrared / Color / Smart Night Vision Modes
Interface	Smart Alarm	Support human detection and enable customization of other intelligent functions.
	Business Functions	Support cell phone remote monitoring; alarm message push; MJPEG capture
	TF card	Local TF card, up to 128G; cloud storage
	Audio I/O	Support Two Way Audio
	Automatic Tracking	Support
	Pan/Tilt Angle	Horizontal:355° & Vertical:90°
	Wi-Fi	WiFi 802.11b/g/n wireless network
General	Material	ABS plastic
	ONVIF	Support 2.4 Onvif Protocol
	Protocol	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP,SMTP
	IE Browser	IE8-11, Google Chrome, Firefox, Safari, Mac Safari
	Operation Temperature	-10℃- + 60℃
	Storage Temperature	10% - 90% RH
	Power Supply	DC 5V±10
	Consumption	MAX 5 W
	Dimensions	100*180mm
	Weight	About 500g
	Protection	IP66