PROVIEW®

8-CH HD Hybrid Digital Video Recorder

SM-XVR108PRO

1080p FULL HD | H.265 | SUPPORT 5IN1 | HDMI | ONVIF

Product Features

- Support H.265/H.264 video formats
- Support audio over coaxial cable
- Support TVI, AHD, CVI, CVBS, IP cameras with adaptive access
- 8 channel BNC input
- Support 1ch HDMI output, 1ch VGA output at up to 1920*1080
- HDMI and VGA simultaneous output
- Long transmission distance over coax cable
- Supports mainstream cameras of ONVIF and RTSP protocols
- Up to 8TB HDD capacity
- Access from smartphone using Guard Live

Proview Indonesia | proview.id | Proview Indonesia | web.proview.id

Model		SM-XVR108PRO
System	Video Compression	H.265/H.264
	Operating	Embedded Linux
Video	Live View Display	HDMI/VGA:1/4/6/8/9/16
	IP Video Input	4-ch
	Analog Video Input	8-ch, BNC
	Max IP Video Input	8-ch
	VGA Output Resolution	1920x1080/60Hz, 1920x1080/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz
	HDMI Output Resolution	
Audio	Audio Input	1CH RCA
	Audio Out	1CH
	Intercom	Yes
Decoding	Encoding	Support AHD input: 1080P@30fps/720P@30fps Support TVI input: 1080P@30fps/720P@30fps Support CVI input: 1080P@30fps/720P@30fps Support CVBS input: 1080P@25fps/720P@25fps
	Recording Resolution	1080P / 720P / D1
	Recording Frame Rate	Mainstream: 1080P@15fps Substream: D1@15fps Mainstream: 720P@25fps Substream: D1@25fps
	Audio Sample Rate	8kHz, 16bit per channel
	Audio Bit Rate	64Kbps per channel
	Decoding Capability	Analog: 8x1080P @15 IP: 2x1080P @30
Operation	Multiplex Operation	Live display & instant playback, record, Slice playback, backup and network
Network	FTP/Schedule/Event Snapshot	FTP/Event snapshot: 8-ch snapshot, up to 704*576 resolution, Schedule snapshot:not supported
	Incoming Bandwidth	32Mbps(Up to 40Mbps after all analog channel conversion)
	Outgoing Bandwidth	64Mbps
	Remote Users	128
	Protocols	TCP/IP, P2P, DHCP, HTTP, HTTPS, DDNS, LAPI, FTP, PPPoE, Multicast
	Browser (Plugin)	Windows: IE (IE10/11), Firefox (version 52.0 and above), Chrome (version 45 and above), Edge (version 79 and above)

Alarm	**General Alarm**	Motion
	Alert Alarm	IP Conflict, Network Disconnected, Disk offline, Disk Abnormal, Illegal Access, Hard Disk Space Low, Hard Disk Full, Recording/Snapshot Abnormal
Client	**Mobile Phone Operating System**	IPhone, Android
	PC Monitoring	Guard Station
Storage	**HDD Number**	1*8TB
	E-SATA	NO
External Interface	**Network Interface**	1 RJ45 10M/100M self-adaptive Ethernet Interface
	USB Interface	2*USB2.0
Other	**Power Supply**	DC12V
	Working Temperature	-10°C ~60°C
	Humidity	10%~90% Humidity