PROVIEW®

2MP

Dual Lens Indoor Wi-Fi PTZ Camera

SM-PR5240-PT

Smart Hybrid

Product Features

- H.265X 2MP Mega Pixels Pan/Tilt WIFI IP Camera
- HD 3.6mm night vision Distance 10-20m
- Support Two-ways Audio intercom
- 5DB antenna wireless camera1 reset button
- Support computer client remote / local viewing
- Add mode : QR code / AP hotspot / Bluetooth Mode;
- Auto Motion Track Could Pan 355 Degree , Tilt 90 Degree
- Support dual-stream, support 2.4GHz WIFI wifi distance 100 meters
- Support TF Card for local storage (Max.128GB);Free one month cloud storage.
- Support multiple mobile monitoring（iOS，Android）Mobile APP：PROVIEW CCTV （5 users remote viewing simultaneously Support automatic color to black function, realize day to night monitoring
- Plug and play, multiple network cloud services open security cloud monitoring
- Support automatic electric shutter function, adapt to different monitor environments.
- Support Alarm Action （Snapshot ，Take a Video, Device Beep）
- Support Motion Alarm（Humanoid detection switch，Show Traces，Perimeter Alert，Cordon，Alert Area）

Proview Indonesia proview.id Proview Indonesia web.proview.id

Model		SM-PR5240-PT
Camera Features	Image Sensor	2.0M 1/3.2" CMOS sensor
	Video Compression	H.265X coding, support dual stream,AVI;0.1M~8Mpbs variable
	Resolution	1920x1080
	Image Output	Mainstream: 1920*1080@10fps sub-stream:640*360@10fps
	Min. Illumination	Color: 1.5 Lux; W/B: 0 Lux with IR LED ON
	Shutter	1/50(1/60) seconds to 1/100,000 seconds
	Focus Length	HD 3.6mm @F2.0（6mm Optional）
	Lens Mode	Fixed Lens
	Infrared LED	4 PCS IR + 4 PCS Warm LED
	Infrared Distance	10-20m
	Day/Night	Color / B&W (IR-CUT)
Interface	Motion Detect	Support
	Video Output	Network
	TF card	Support external 128 GB Micro TF card
	Audio I/O	Support Two Way Audio
	Automatic Tracking	Support
	Pan/Tilt Angle	Horizontal:355° & Vertical:90°
	Wi-Fi	WiFi 802.11b/g/n wireless network
General	Material	ABS plastic
	ONVIF	No
	Protocol	No
	IE Browser	No
	Operation Temperature	-10℃-＋60℃
	Storage Temperature	10% - 90% RH
	Power Supply	DC 5V±10
	Consumption	MAX 5 W
	Dimensions	100*180mm
	Weight	About 500g
	Protection	IP66